



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 11/04/04

## DAP® Blacktop Asphalt VOC-Compliant Filler & Sealer

- For quick and easy repairs to asphalt surfaces
- Perfect for playgrounds, driveways, pavement and parking lots
- Easy-to-use
- Durable elastic seal
- Weatherproof
- Water Clean-up

**Packaging:** 10.1 fl. oz.  
**Colors:** Black  
**UPC Number:** 27065

### Company Identification:

Marketed by: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224  
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.  
Order Information: 800-327-3339  
Fax Number: 410-534-2650  
Also, visit the DAP website at [www.dap.com](http://www.dap.com).

### Product Description:

DAP® Blacktop Asphalt VOC-Compliant Filler & Sealer is an easy-to-use product for the repair of masonry and bituminous paving cracks or any other place where paving faults require a durable elastic seal. Repairs are ready for traffic 24 following application, when directions are properly followed.

### Surface Preparation & Application

1. Apply when temperatures are above 50°F and no rain or freezing temperatures are expected for 24 hours.
2. Crack surfaces should be free of grease, oil and other foreign matter. Sweep or blow surface with compressed air to remove all mud, dirt, dust and other loose debris.
3. Trim nozzle to desired bead size.
4. Load cartridge into caulking gun.
5. Puncture inner foil seal.
6. Fill cracks with sealant.
7. Allow to cure for at least 24 hours before returning area to service. Blacktop Asphalt VOC-Compliant Filler & Sealer cures in approximately 24 hours under normal conditions and if rain is not imminent.
8. Keep product from freezing. Store in heated area during cold weather. Store above 50° F.

**Physical & Chemical Characteristics:**

Color:	Black
Consistency:	Thick paste
Cure Time:	24 hours
Shelf Life:	1 Year
Application Temperature:	Above 50°F
Coverage:	55 linear feet at 3/16” bead.
MSDS No:	79955 001

**Clean Up:**

Wet product can be cleaned up with soap and water. Cured material must be cut or scraped away.

**Safety:**

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at [www.dap.com](http://www.dap.com) or by calling 888-DAP-TIPS.

**Warranty Information:**

If you are not satisfied with product performance when used as directed, return sales receipt and used container to DAP Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD, 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.